

Nylon Hoses / Nylonschläuche



Order No Bestellnr.	Internal Dia. Innendurchmesser		Outside Dia Außendurchmesser mm	Max. Working Pressure at 20°C Max. Betriebsdruck 20°C Bar	Bursting Pressure at 20°C Berstdruck 20°C Bar	Length Länge m.	Colour Farbe	
	mm	Inch.						
NLH - 06	6	1/4	11.5	7	21	100	Neutral	Transparent
NLH - 06B	6	1/4	11.5	7	21	100	Blue	Bleu
NLH - 06R	6	1/4	11.5	7	21	100	Red	Rouge
NLH - 08	8	5/16	13.8	7	21	100	Neutral	Transparent
NLH - 08B	8	5/16	13.8	7	21	100	Blue	Bleu
NLH - 08R	8	5/16	13.8	7	21	100	Red	Rouge
NLH - 10	9.5	3/8	15	7	21	100	Neutral	Transparent
NLH - 10B	9.5	3/8	15	7	21	100	Blue	Bleu
NLH - 10R	9.5	3/8	15	7	21	100	Red	Rouge
NLH - 13	12.7	1/2	18	7	21	100	Neutral	Transparent
NLH - 13B	12.7	1/2	18	7	21	100	Blue	Bleu
NLH - 13R	12.7	1/2	18	7	21	100	Red	Rouge
NLH - 16	16	5/8	23	7	21	100	Neutral	Transparent
NLH - 19	19	3/4	26.4	7	21	100	Neutral	Transparent
NLH - 23	25	1	33.4	7	21	100	Neutral	Transparent

Structure

PVC hose with polyester reinforcement kink resistant and flexible. Also available in food industry

Working Temperature Range

Static conditions : -20°C to + 65°C
Dynamic conditions : - 5°C to + 50°C

Structure

PVC Schläuche mit Polyesterbewehrung, ist knickbeständig und biegsam. Anwendbar in Lebensmittelindustrie.

Température d'utilisation

en Statique : -20°C to + 65°C
en Dynamique : - 5°C to + 50°C