



Moduler Link and Accessories - Segment und Zubehör

Interchangeability - Kompatibilität
CEJN Multi Link

Temperature Range - Temperaturbereich
-30°C +100°C (-22°F +212°F)

Working Pressure - Betriebsdruck
0 - 10 bar (0 - 145 PSI)

Material - Material
Brass Nickel Plated
Messing vernickelt



Female Threaded Center Module
Zwischensegment, Innengewinde

Connection
Anschlüsse

Order No
Bestellnr.

G 1/2"

117 RK 000 - D21

NPT 1/2"

117 RK 000 - N21



Female Threaded Outlet Module
Endsegment, Innengewinde

G 1/2"

117 RK D21 - D21

NPT 1/2"

117 RK N21 - N21



Inlet Module
Anfangssegment

G 1/2"

117 RK D21 - 000

NPT 1/2"

117 RK N21 - 000



Stop Valve
Absperrventil

117 RK A00 - 000



Pressure Plug With O-Ring
Stopfen mit O-Ring

G 1/2"

KTS 21

NPT 1/2"

KTT 21



Hose Connection 11 x 16 mm
Schlauchanschluss 11 x 16 mm

R 1/2"

PUR 21 - 16

NPT 1/2"

PUN 21 - 16



Hose (PUR) 11 x 16 mm 100 m-Rol
Schlauch (PUR) 11 x 16 mm 100 m-Rolle

PUR 100.1116

SERIE 117-RK

